

The SENCO FinishPro® 25XP has redefined the brad nailer category! This lightweight, power-packed nailer is loaded with all the features you need, plus a few more. The FinishPro 25XP drives both slight and medium headed 18 ga. brads from 5/8" to 2-1/8" into the hardest woods. The "on-tool" power adjustment allows the user to increase power by 30%. All this, plus SENCO's exclusive NeverLube® design to keep your work surface oil free.



## Applications

Molding and decorative trim, furniture trim, window beading, blind pinning of upholstered and trim panels, rattan, scribe, molding, cabinets, drawers and picture frame assembly

## Features and Benefits



- Five-year limited warranty
- Comfort and convenient features include: overmold comfort grip, overmold trigger, "on-tool" power adjustment, 360° adjustable exhaust, and belt hook
- Lightweight at 2.7 lbs for easy maneuvering and all day work
- Drives slight and medium head 18 gauge brads from 5/8" (15mm) to 2-1/8" (55mm)
- On-tool power adjustment to lengthen the life of the tool when used primarily with shorter fasteners
- Wrenches onboard to make the adjustment fast and easy
- NeverLube® technology – no lubrication required

## Specifications

Item#.....	760102N
Reg. Operating Pressure.....	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 cycles per min.) ...	1.92 scfm
Air Inlet.....	1/4" NPT
Tool Weight .....	2.7 lbs (1.2 kg)
Height.....	9.9" (251 mm)
Length .....	9.8" (249 mm)
Width .....	2.2" (56 mm)
Fastener Capacity.....	110

## Fastener Specifications

Gauge.....	18
Fastener Range .....	5/8" – 2 1/8"
Finish.....	Galvanized
Collation.....	Straight glued strip



## Available 18 Ga. Genuine SENCO Fasteners

Length	Item Code	Count	Finish	Package
5/8"	AY10EAA	5M	Galv	Box
3/4"	AY11EAA	5M	Galv	Box
1"	AY13EAA	5M	Galv	Box
5/8"	AX10EAA	5M	Galv	Box
1"	AX13EAA	5M	Galv	Box
1 1/4"	AX15EAA	5M	Galv	Box
1 1/2"	AX17EAA	5M	Galv	Box
1 5/8"	AX18EAA	5M	Galv	Box
1 3/4"	AX19EAA	5M	Galv	Box
2"	AX21EAA	5M	Galv	Box
2 1/8"	AX22EAA	5M	Galv	Box
1"	A201009	1M	Galv	Clamshell
1 1/4"	A201259	1M	Galv	Clamshell
1 1/2"	A201509	0.8M	Galv	Clamshell
2"	A202009	0.8M	Galv	Clamshell

### Variety Packs:

5/8" - 1 1/4"	A209809	1.2M	Galv	Clamshell
1" - 2"	A209909	1.2M	Galv	Clamshell



### \* On-tool Power Adjustment



The FinishPro 25XP has the unique ability to increase or decrease the power output with a simple adjustment located on the tool. The Standard setting for the FinishPro 25XP allows you to accomplish most jobs. This is the factory setting. The Turbo setting on the FinishPro 25XP gives you a 30% increase in power for longer brads and harder wood applications. For complete details on how to operate the power adjustment, please refer to the operators manual.

Choose the right trigger system for your specific needs!

**Sequential Actuation Trigger** (also known as restrictive trigger or trigger fire) operates in the following a sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

**Contact Actuation Trigger** (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on trigger systems and how Senco will save you time, reduce costs, and increase quality, call our toll-free Action Line: 800-543-4596 to find your nearest Authorized Senco Dealer, Distributor or visit our web site at: [www.senco.com](http://www.senco.com)