



MODEL M3

Applications:

Framing applications in mobile home manufacturing, pre-assembled building components, sheathing, sub-flooring, roof deck, door and window units, furring to light concrete blocks, furniture frame assembly, pallets, crating.

M3 Tool Specifications:

Tool Weight: $7\frac{13}{16}$ lbs. Height: $11\frac{1}{8}$ " (with Senco-Matic $12\frac{1}{16}$ "). Length: $12\frac{13}{16}$ ". Lip Length: $\frac{1}{2}$ ". Staple Capacity: 110-plus, 15 gauge, in various lengths. Optional Driving: Senco-Matic, safety touch trip or trigger. Reg. Operating Pressure: 80-110 p.s.i.g.

Fastener Specifications:

Crown	Gauge	Width	Thickness	Length
$\frac{3}{16}$ "	15	.074"	x .067"	$1\frac{1}{4}$ ", $1\frac{1}{2}$ ", $1\frac{3}{4}$ ", 2", $2\frac{1}{4}$ ", $2\frac{1}{2}$ "

Metal: Bright Basic or Galvanized



MODEL M2

Applications:

Pallets and crate assembly, mobile home manufacturing, furniture frame assembly, sheathing, sub-flooring, roof deck, window units, pre-assembled components for home construction, crating.

M2 Tool Specifications:

Tool Weight: $6\frac{7}{8}$ lbs. Height: $11\frac{1}{8}$ " (with Senco-Matic 12"). Length: $12\frac{1}{2}$ ". Lip Length: $1\frac{1}{4}$ ". Staple Capacity: 140-plus, 16 gauge, in various lengths. Optional Driving: Senco-Matic, safety touch trip or trigger. Reg. Operating Pressure: 90-110 p.s.i.g.

Fastener Specifications:

Crown	Gauge	Width	Thickness	Length
$\frac{3}{16}$ "	16	.062"	x .055"	$1\frac{1}{4}$ ", $1\frac{1}{2}$ ", $1\frac{3}{4}$ ", $1\frac{3}{8}$ ", $1\frac{7}{8}$ ", 2"

Metal: Std. Carb. Galv.



MODEL M1

Applications:

Furniture frame assembly, mobile home manufacturing, sheathing, sub-flooring, roof deck, cedar shingles, aluminum siding, fascia and soffit, particle board, lathing, window units, crating, wooden boxes, wood fences.

M1 Tool Specifications:

Tool Weight: $6\frac{1}{4}$ lbs. Height: $9\frac{3}{8}$ " (with Senco-Matic $10\frac{1}{4}$ "). Length: $12\frac{1}{2}$ ". Lip Length: $\frac{3}{4}$ ". Staple Capacity: 140-plus, 16 gauge, in various lengths. Optional Driving: Senco-Matic, safety touch trip or trigger. Reg. Operating Pressure: 90-100 p.s.i.g.

Fastener Specifications:

Crown	Gauge	Width	Thickness	Length
$\frac{3}{16}$ "	16	.062"	x .055"	1", $1\frac{1}{8}$ ", $1\frac{1}{4}$ ", $1\frac{3}{8}$ ", $1\frac{1}{2}$ ", $1\frac{3}{4}$ ", $1\frac{7}{8}$ "

Metal: Std. Carb. Galv.

NOTE: Senco 18 gauge (.050" x .044") $1\frac{1}{4}$ ", $1\frac{1}{2}$ ", and $1\frac{3}{4}$ " bright basic wire staples can be driven by modified M-1—consult your Senco Representative.

