

Unique systems that clamps material together, holding and supporting it for the life of the product you manufacture. The versatile SENCOR® SC1XP tool drives three sizes of fasteners for stronger joints and fewer assembly operations. It is designed to do a wide range of wood fastening applications better, faster and cheaper.



### Specifications

Item#.....	220101N
Sequential actuation trigger	
Reg. Operating Pressure.....	80-110 psi (5.5 - 7.5 bar)
Air Consumption (60 cycles per min.) ...	3.8 scfm
Air Inlet.....	3/8" NPT
Tool Weight .....	6.3 lbs (2.8 kg)
Height.....	9.8" (249 mm)
Length .....	12.7" (322 mm)
Fastener Capacity.....	120

### Fastener Specifications

Gauge.....	25
Fastener Range .....	5/16" - 9/16"
Crown.....	7/16"
Finish.....	Bright Basic
Collation.....	Taped strip

Length	Item Code	Carton Count	Finish
5/16"	Y05BFA	3.0M	Bright
7/16"	Y07BFA	3.0M	Bright
9/16"	Y09BFAN	3.0M	Bright

Crown: 7/16 (11.1)  
 Thickness: .020  
 Gauge: 25

### Applications

Butt Joints, cabinets, caskets, curios, mirror and picture frames.

### Features and Benefits

- Five-year limited warranty
- Senclamp fasteners pull the joint together during driving for a tight, permanent fit
- Consistent drives even in hard woods
- Eliminate milling, doweling, clamping, screwing and other time-consuming, cost-adding operations
- The Senclamp high-carbon steel fastener derives added strength from its special webbed design

\*Choose the right actuation mode!

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.



Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on trigger systems and how SENCOR will save you time, reduce costs, and increase quality, call our toll-free Action Line: 800-543-4596, or visit our web site at: [www.senco.com](http://www.senco.com).