

SHF50 is the industry's only pneumatic hardwood flooring nailer with a work contact safety, which is activated when the tool is positioned on the floor tongue - not by depressing a trigger.




Specifications

Item#.....	710001N
Reg. Operating Pressure.....	70-120 psi (4.8 - 8.3 bar)
Air Inlet.....	3.8" NPT
Tool Weight	12 lbs (5.5 kg)
Height.....	17.75" (451 mm)
Length	16.25" (413 mm)
Fastener Capacity.....	110

Fastener Specifications

Fastener	L type cleat nail
Fastener Range	1½, 1¾ and 2"
Finish.....	Bright Basic
Collation.....	Glued strip



Applications

For the installation of 1/2" (12mm) to 33/32" (26mm) hardwood flooring. (1/2" applications require optional adapter.)

Features and Benefits

- Easy on the arm, requiring a single strike of only 4 lbs. of swing weight to drive fastener.
- Mallet-actuated firing simultaneously sets floor boards (tongue into groove) and drives cleat nail at an ideal 45° angle
- Mallet included
- 1-year limited warranty



For additional information on how Senco will save you time, reduce costs, and increase quality, call us at 1-800-543-4596 to find your nearest Authorized Senco Dealer or Distributor or visit our web site at: www.senco.com

Sequential Actuation Trigger (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.