



MODEL SN4

Applications:

Construction framing, wood-to-concrete, truss building, sub-flooring, sidewall sheathing and roof deck application on-site and in-plant. Crate and box assembly. Industrial pallet making. Furniture frame assembly and cabinet work.

SN4 Tool Specifications:

Tool Weight: 10 $\frac{5}{8}$ lbs. Height: 14.8". Length: 15.7". Lip Length: $\frac{7}{8}$ ". Nail Capacity: 50-70, depending upon gauge, cohered in easy-loading strips. Optional Driving: safety touch trip or trigger. Reg. Operating Pressure: 100 p.s.i.g.

Fastener Specifications:

Shank Type	Shank Gauge	Shank Dia.	Penny Weight	Length
Smooth	11 $\frac{1}{2}$.113"	6d,7d,8d	2", 2 $\frac{1}{4}$ ", 2 $\frac{1}{2}$ "
Smooth	10 $\frac{1}{4}$.131"	10d,12d,16d	3", 3 $\frac{1}{4}$ ", 3 $\frac{1}{2}$ "
Ring	11 $\frac{1}{2}$.113"	6d,8d	2", 2 $\frac{3}{8}$ "
Screw	12	.105"	6d,7d,8d	2", 2 $\frac{1}{4}$ ", 2 $\frac{1}{2}$ "
Screw	11	.120"	10d	3"



MODEL SN2

Applications:

Sub-flooring, bridging, roof deck, sheathing, siding, light framing and component assembly in manufactured and mobile homes and on-site construction. Furniture frame assembly. Crate, box and light-weight pallet construction, fencing.

SN2 Tool Specifications:

Weight: 7 $\frac{9}{16}$ lbs. Height: 11 $\frac{1}{2}$ ". Length: 14 $\frac{1}{2}$ ". Lip Length: $\frac{5}{32}$ ". Nail Capacity: 60-90, depending upon gauge, cohered in easy-loading strips. Optional Driving: safety touch trip or trigger. Reg. Operating Pressure: 80-100 p.s.i.g.

Fastener Specifications:

Shank Type	Shank Gauge	Shank Dia.	Penny Weight	Length
Smooth	13	.0915"	6d,7d,8d	1 $\frac{1}{8}$ ", 2 $\frac{1}{8}$ ", 2 $\frac{3}{8}$ "
Smooth	11 $\frac{1}{2}$.113"	6d,7d,8d,10d	2", 2 $\frac{1}{4}$ ", 2 $\frac{1}{2}$ ", 3"
Ring	11 $\frac{1}{2}$.113"	6d,8d	2", 2 $\frac{3}{8}$ "

