



AirFree™ 41 Comparison chart

BATTERY POWERED NAILERS

	15 ga	16 ga	16 ga
Brand	<i>SENCO® AirFree™</i>	<i>Paslode</i>	<i>Paslode</i>
Model No.	<i>AirFree™ 41</i>	<i>IM250 II</i>	<i>IM250A</i>
Suggested Retail		MSRP \$399.00 (US\$)	MSRP \$399.00 (US\$)
Fastener Range	15 ga. 1-1/4 – 2-1/2"	16 ga. 3/4" – 2-1/2"	16 ga. 1-1/4" – 2-1/2"
Warranty	1 yr.	1 yr.	1 yr.
Weight	7.5 lbs.	5.5 lbs.	4.9 lbs.
Length	12-7/8"	11-1/2"	10-3/4"
Width	4-3/8"	Unavailable	3-1/4"
Height	13"	12-1/2"	11-1/2"
Fastener Capacity	110	100	100
Depth of Drive	Electronic	Thumbwheel	Thumbwheel
Grip	Top Over-Mold	None	Top Over-Mold
Battery	2-14.4V NiCad	1-6V	1-6V
Fuel	Not Required	\$5.50/canister	\$5.50/canister
NoMar pad	Removable	Removable	(2) Removable
Case	Plastic	Plastic	Plastic
Adjustable Exhaust	Not Required	No Adjustment Fan Aided	No Adjustment Fan Aided
Power	Electronically Controlled 156-396 in/lbs.	328 in/lbs.	328 in/lbs.
Charger	Dual Chemistry (NiCad/NiMh) 1-Hour Fast Charger	2-hour Charger	2-hour Charger
Easy Clear	Quick Release Nose Latch	Nose Latch	Nose Latch
Fastener/Charge	Up to 750	1,200-Fuel Cell 4,000-Battery	1,200-Fuel Cell 4,000-Battery
Magazine Position	Angled In-Line	Straight In-Line	Angled In-Line
Reload Indicator	Yes	Yes/10-Nail Lockout	Yes/10-Nail Lockout
Trigger Actuation	Sequential	Sequential	Sequential
Other	Belt Hook Belt Drive for quiet operation	Not recommended for use at altitudes above 5,000 feet, or in temperatures below 20°F/-7°C.	Not recommended for use at altitudes above 5,000 feet, or in temperatures below 20°F/-7°C.