



Specifications:

Item#: 4N0001N
 Tool Weight: 2.9 lbs (1.3 kg)
 Height: 9.6" (228.6 mm)
 Length: 9" (244 mm)
 Lip Length: 1" (25 mm)
 Pin Capacity: 115
 Range: 1" – 2"
 Gauge: 23
 Reg. Operating Pressure: 70-95 psi (4.8-6.5 bar)
 Single Activation
 Hose Fitting: ¼" NPT

This 23 ga. Micro Pinner is the perfect tool for your intricate finish and trim projects. The pins fasten the smallest of decorative trim securely and leave a nearly invisible hole – no splitting or puttying. The FinishPro® 11 drives 1" – 2", 23 gauge headless pins.

Applications:

Cabinet, decorative trim, glazing bead, carvings, picture frames and molding.

Features and Benefits:

- Extra power – For use with hard wood
- Hardened alloy steel driver – For durability
- Fast side load magazine with easy open latch
- Rear exhaust – Directs oil and dust away from work surface
- Switchable trigger with lock
- Stretch comfort grip – For comfort and control
- EZ-Clear™ latch
- No mar pad
- Belt hook
- Includes case, fittings, repair tools and tool oil

Fastener Specifications:

Drives 23 gauge, headless micro pins from 1" – 2" in length.

23 Ga. Headless Pins

Length	Item Code	Carton Count	Finish
1 0	A101009	2.6M	Galv
1 ¼	A101259	2.6M	Galv
1 ¾	A101379	2.6M	Galv
1 ½	A101509	2.6M	Galv
2 0	A102009	2.6M	Galv



Sequential Actuation Trigger (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation Trigger (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions or log on to www.senco.com or call 1-800-543-4596 for more information on SENCO's trigger systems. Choose the right trigger system for your specific needs!

For additional information on how Senco will save you time, reduce costs, and increase quality, call us at 1-800-543-4596 to find your nearest Authorized Senco Dealer or Distributor or visit our web site at: www.senco.com