

Unique systems that clamp material together, holding and supporting it for the life of the product you manufacture. The versatile SENCO® SC1XP tool drives three sizes of fasteners for stronger joints and fewer assembly operations. It is designed to do a wide range of wood fastening applications better, faster and cheaper.




Tool Specifications:

Item #: 220101N Sequential actuation trigger
 Tool Weight: 6.3 lbs (2.9 kg)
 Height: 10" (249 mm)
 Length: 13" (322 mm)
 Senclamp Capacity: 120
 Reg. Operating Pressure: 80-120 psig
 Mode of Operation: Sequential Actuation

Fastener Specifications:

7/16" Crown. 25-Gauge. Senclamp. 5/16"—9/16" Lengths.
 Capacity 120



Crown: 7/16 (11.1)
 Thickness: .020
 Gauge: 25

Length	Item Code	Carton Count	Finish
5/16	Y05BFA	3.0M	Bright
7/16	Y07BFA	3.0M	Bright
9/16	Y09BFAN	3.0M	Bright

Applications:

Butt Joints, cabinets, caskets, curios, mirror and picture frames.

Features and Benefits:

- Senclamp fasteners pull the joint together during driving for a tight, permanent fit
- Consistent drives even in hard woods
- Eliminate milling, doweling, clamping, screwing and other time-consuming, cost-adding operations
- The Senclamp high-carbon steel fastener derives added strength from its special webbed design

Choose the right trigger system for your specific needs!

Sequential Actuation Trigger (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation Trigger (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.



Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on trigger systems and how SENCO will save you time, reduce costs, and increase quality, call our toll-free Action Line: 800-543-4596 to find your nearest Authorized Senco Dealer, Distributor or visit our web site at: www.senco.com