



The versatile SENCOR® SC2 tool drives three sizes of fasteners for stronger joints and fewer assembly operations. It is designed to do a wide range of wood fastening applications better, faster and cheaper.

## Applications:

Butt Joints, cabinets, caskets, curios, mirror and picture frames, pallets and pallet repair, trusses, crate and box assembly

## Features and Benefits:

- Added strength for larger butt joints
- Powerful for hard and dense material
- Eliminate gluing, milling, doweling, screwing and clamping
- Sencor® corrugated fasteners provide twice the joint strength of ordinary fasteners

### Choose the right trigger system for your specific needs!

**Sequential Actuation Trigger** (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

**Contact Actuation Trigger** (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.


## Tool Specifications:

Item #: 470001N Sequential Actuation Trigger  
 Tool Weight: 6.9 lbs (3.1 kg)  
 Height: 9¾" (248 mm)  
 Length: 13" (322 mm)  
 Fastener Capacity: 106  
 Reg. Operating Pressure: 90-120 psig  
 Mode of Operation: Sequential Actuation

## Fastener Specifications:

1" Crown. 25-Gauge. Sencor® corrugated fasteners.  
 ¼", ⅜" and ½" Lengths. Capacity 106

Length	Item Code	Carton Count	Finish
¼"	X04NRA	8.0M	Bright
⅜"	X06NRA	5.0M	Bright
½"	X08NRA	4.0M	Bright



Crown: 1 (25.4)  
 Gauge: 25  
 Thickness: .020



Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on trigger systems and how SENCOR will save you time, reduce costs, and increase quality, call our toll-free Action Line: 800-543-4596 to find your nearest Authorized Senco Dealer, Distributor or visit our web site at: [www.senco.com](http://www.senco.com)