



08C300WK

SCREW SPECIFICATIONS

Screw Gauge	#8
Length	3"
Recess	#2 Phillips
Head	Bugle
Point	Drill
Thread Type	2/3 Fine (18 TPI)
Finish	Exterior



#2 Phillips Drive



Bugle Head



Drill

Exterior Drill Point Drywall Screw

Drywall to heavy steel fastener

APPLICATIONS

- Designed for attaching fiber reinforced gypsum sheathing (35-90 mil)



FEATURES AND BENEFITS

- Phillips recess provides smooth engagement capabilities with moderate torque transmission
- Bugle head provides consistent penetration without damaging the paper
- Fine threads provide improved holding power and thread-forming capability when driving into steel
- Forged and hardened drill point
- Exterior finish exceeds 1000 hours salt spray per ASTM B117

INSTALLATION GUIDELINES

- Use a screwdriver with a precise depth-sensitive clutch and speeds of up to 5000 RPM
- Overdriving may cause a weak connection or thread strip-out
- The drive is finished when the screw is just below the work surface without tearing the paper
- Three full threads must extend past the base metal for an acceptable connection

08C300WK

Exterior Drill Point Drywall Screw

Drywall to heavy steel fastener



ORDERING INFORMATION

Item Code	Gauge	Length	Thread	Finish	Quantity	Drive Type	Point	Head
08C300WK	#8	3"	2/3 Fine	Exterior	1000 Box	#2 Philips	Drill	Bugle

TECHNICAL INFORMATION

Ultimate Tensile (lbs)*	Torsional Strength (inlb)*
1110	72

*Figures represent ultimate average test results. An appropriate safety factor must be applied for design purposes

Finish	Testing Standard	Corrosion Resistance
Exterior	ASTM B117 Salt Spray Test	Over 1000 Hours without red rust

Length (L):	3 in
Head Diameter (A):	0.32 in
Head Height (H):	0.18 in
Major Diameter (D):	0.16 in
Minor Diameter (B):	0.12 in
Length of Drill (S):	0.19 in
Diameter of Drill (M):	0.13 in
Length of Thread (L1):	2.00 in
Threads Per Inch (TPI):	18

