



08F175YKX

## SCREW SPECIFICATIONS

Screw Gauge	#8
Length	1¾"
Recess	Rex Drive
Head	Flat
Point	Sharp
Thread Type	Double Thread
Finish	Yellow Zinc



Rex Drive



Flat Head



Sharp Point

## Interior Wood Screw

Wood to wood fastener

### APPLICATIONS

- Interior wood to wood applications
- Subflooring
- Framing



### FEATURES AND BENEFITS

- Asymmetric double thread design reduces installation time while improving holding power
- Rex drive recess provides smooth engagement with high torque transmitting capability reducing operator fatigue, and extending bit life
- Flat head provides strong holding power for wood applications
- Ultra sharp point quickly penetrates wood reducing drive time
- Yellow zinc finish

### INSTALLATION GUIDELINES

- Use a screwdriver with a torque controlled or precise depth-sensitive clutch and speeds of up to 5000 RPM
- Overdriving may cause a weak connection or thread strip-out
- The drive is finished when the screw is just below the work surface

# 08F175YKX

## Interior Wood Screw

Wood to wood fastener



### ORDERING INFORMATION

Item Code	Gauge	Length	Thread	Finish	Quantity	Drive Type	Point	Head
08F175YKX	#8	1 3/4"	2/3 Double	Yellow Zinc	1000 Box	Rex Drive	Sharp	Flat

### TECHNICAL INFORMATION

Ultimate Tensile (lbs)*	Torsional Strength (lbs-in)*
2010	88

\*Figures represent ultimate average test results. An appropriate safety factor must be applied for design purposes

Finish	Testing Standard	Corrosion Resistance
Yellow Zinc	ASTM B117 Salt Spray Test	Over 48 Hours without red rust

#### Reference Dimension

Length (L):	1.75 in
Thread Length (L1):	1.17 in
Head Diameter (A):	0.32 in
Head Height (H):	0.18 in
Major Diameter (D):	0.17 in
Minor Diameter (B)	0.12 in
Threads Per Inch (TPI):	10 threads/in

