



08G150CTLDSS

## SCREW SPECIFICATIONS

Screw Gauge	#8
Length	1 1/2"
Recess	#2 Square
Head	Flat
Point	Sharp
Thread Type	Double Thread
Finish	Clear Zinc



#2 Square



Flat



Sharp

## Sharp Point Sheathing Screw

Sheathing to light steel fastener

### APPLICATIONS

- Designed for attaching sheathing to 25ga to 20ga steel



### FEATURES AND BENEFITS

- Square recess provides excellent torque transmission for high torque applications
- Flat head provides strong holding power for most wood applications.
- Double thread design reduces installation time and maintains the holding power of fine threads
- Ultra sharp point quickly penetrates light gage steel reducing drive time
- Clear zinc finish

### INSTALLATION GUIDELINES

- Use a screwdriver with a torque controlled or precise depth-sensitive clutch and speeds of up to 5000 RPM
- Overdriving may cause a weak connection or thread strip-out of the steel
- The drive is finished when the screw is below the work surface
- Three full threads must extend past the base metal for an acceptable connection

# 08G150CTLDSS

## Sharp Point Sheathing Screw

Sheathing to light steel fastener



### ORDERING INFORMATION

Item Code	Gauge	Length	Thread	Finish	Quantity	Drive Type	Point	Head
08G150CTLDSS	#8	1 1/2"	Double	Clear Zinc	1000 Tub	#2 Square	Sharp	Flat

### TECHNICAL INFORMATION

Ultimate Tensile (lbs)*	Torsional Strength (lbs-in)*
2165	58

\*Figures represent ultimate average test results. An appropriate safety factor must be applied for design purposes

Finish	Testing Standard	Corrosion Resistance
Clear Zinc	ASTM B117 Salt Spray Test	Over 24 Hours without red rust

#### Reference Dimensions

Length (L):	1.50 in
Head Diameter (A):	0.35 in
Head Height (H):	0.20 in
Major Diameter (D):	0.16 in
Minor Diameter (B):	0.12 in
Threads Per Inch (TPI):	14 threads/in

