



08L125CBLCTS

## SCREW SPECIFICATIONS

Screw Gauge	#8
Length	1 1/4"
Recess	#2 Square
Head	Flat
Point	Type 17
Thread Type	Coarse
Finish	Clear Zinc



#2 Square



Flat with nibs



Type 17

## Type 17 Point, Flat Head Flooring Screw Flooring to wood fastener

### APPLICATIONS

- Wood to wood
- Flooring



### FEATURES AND BENEFITS

- Square recess provides excellent torque transmission for high torque applications
- Flat head provides strong holding power for most wood applications
- Coarse threads are ideal for use in wood connections
- Type 17 point is designed for wood fastening applications and speeds penetration in hard materials
- Clear zinc finish

### INSTALLATION GUIDELINES

- Use a screwdriver with a precise depth-sensitive clutch and speeds of up to 5000 RPM
- Overdriving may cause a weak connection or thread strip-out of the material
- The drive is finished when the screw is below the work surface

# 08L125CBLCTS



## Type 17 Point, Flat Head Flooring Screw

Flooring to wood fastener

### ORDERING INFORMATION

Item Code	Gauge	Length	Thread	Finish	Quantity	Drive Type	Point	Head
08L125CBLCTS	#8	1 1/4"	Coarse	Clear Zinc	4000 Box	#2 Square	Type 17	Flat with nibs

### TECHNICAL INFORMATION

Ultimate Tensile (lbs)*	Torsional Strength (lbs-in)*
1980	56

\*Figures represent ultimate average test results. An appropriate safety factor must be applied for design purposes

Finish	Testing Standard	Corrosion Resistance
Clear Zinc	ASTM B117 Salt Spray Test	Over 24 Hours without red rust

#### Reference Dimensions

Length (L):	1.25 in
Head Diameter (A):	0.32 in
Head Height (H):	0.17 in
Major Diameter (D):	0.17 in
Minor Diameter (B):	0.11 in
Thread Length (L1):	0.83 in
Flute Length (S):	0.41 in
Threads Per Inch (TPI):	11 threads/in

