



10F200Y

## SCREW SPECIFICATIONS

Screw Gauge	#10
Length	2"
Recess	#2 Square
Head	Flat
Point	Sharp
Thread Type	2/3 Coarse
Finish	Yellow Zinc



#2 Square



Flat



Sharp

## Sharp Point, Interior Wood Screw

Wood to wood fastener

### APPLICATIONS

- Interior wood to wood
- Subfloor
- Framing



### FEATURES AND BENEFITS

- Square recess provides excellent torque transmission for high torque applications
- Flat head provides strong holding power for most wood applications
- 2/3 thread prevents gaps between the sheathing and support studs which can cause squeaks
- Ultra sharp point quickly penetrates wood reducing drive time
- Yellow zinc finish

### INSTALLATION GUIDELINES

- Use a screwdriver with a torque controlled or precise depth-sensitive clutch and speeds of up to 5000 RPM
- Overdriving may cause a weak connection or thread strip-out of the wood
- The drive is finished when the screw is below the work surface

# 10F200Y

## Sharp Point, Interior Wood Screw

Wood to wood fastener



### ORDERING INFORMATION

Item Code	Gauge	Length	Thread	Finish	Quantity	Drive Type	Point	Head
10F200Y	#10	2"	2/3 Coarse	Yellow Zinc	800 Tub	#2 Square	Sharp	Flat

### TECHNICAL INFORMATION

Ultimate Tensile (lbs)*	Torsional Strength (lbs-in)*
2920	96

\*Figures represent ultimate average test results. An appropriate safety factor must be applied for design purposes

Finish	Testing Standard	Corrosion Resistance
Yellow Zinc	ASTM B117 Salt Spray Test	Over 48 Hours without red rust

#### Reference Dimensions

Length (L):	2.00 in
Thread Length (L1):	1.33 in
Head Diameter (A):	0.34 in
Head Height (H):	0.18 in
Major Diameter (D):	0.20 in
Minor Diameter (B):	0.14 in
Threads Per Inch (TPI):	8 threads/in

