



07Q125PBQ

SCREW SPECIFICATIONS

Screw Gauge	#7
Length	1 ¼"
Recess	#2 Square
Head	Trim with Nibs
Point	Sharp
Thread Type	High Low
Finish	Gray Phosphate



#2 Square



Trim with Nibs



Sharp

Trim Head Underlayment Screw

High speed wood to wood fastener

APPLICATIONS

- Designed for high speed wood to wood applications
- Crating
- Pallets



FEATURES AND BENEFITS

- Square recess provides excellent torque transmission for high torque applications
- Trim head reduces chance of cracking in brittle materials, and the nibs help seat the head in dense materials
- High-low thread for high speed installation and improved holding power
- Ultra sharp point quickly penetrates wood reducing drive time
- Gray phosphate is an economical rust inhibitor meant for interior applications

INSTALLATION GUIDELINES

- Use a screwdriver with a torque controlled or precise depth-sensitive clutch and speeds of up to 5000 RPM
- Overdriving may cause a weak connection or thread strip-out of the wood
- The drive is finished when the screw is below the work surface

07Q125PBQ



Trim Head Underlayment Screw
High speed wood to wood fastener

ORDERING INFORMATION

Item Code	Gauge	Length	Thread	Finish	Quantity	Drive Type	Point	Head
07Q125PBQ	#7	1 1/4"	High-Low	Gray Phosphate	4000 Box	#2 Square	Sharp	Trim with Nibs

TECHNICAL INFORMATION

Ultimate Tensile (lbs)*	Torsional Strength (lbs-in)*
1200	28

*Figures represent ultimate average test results. An appropriate safety factor must be applied for design purposes

Finish	Testing Standard	Corrosion Resistance
Gray Phosphate	ASTM B117 Salt Spray Test	Over 24 Hours without red rust

Reference Dimension

Length (L):	1.25 in
Head Diameter (A):	0.27 in
Head Height (H):	0.18 in
Major Diameter (D):	0.17 in
Minor Diameter (B):	0.09 in
Threads Per Inch (TPI):	17 threads/in

