



08F200YBTHSS

SCREW SPECIFICATIONS

Screw Gauge	#8
Length	2"
Recess	#2 Square
Head	Trim with Nibs
Point	Sharp
Thread Type	High-Low
Finish	Yellow Zinc



#2 Square



Trim with Nibs



Sharp

Interior Trim Head with Nibs Screw

Engineered sheathing to wood

APPLICATIONS

- Designed for harder and more dense sheathing applications
- Subflooring



FEATURES AND BENEFITS

- Square recess provides excellent torque transmission for high torque applications
- Trim head with nibs help seat the head in dense materials
- High-low thread for high speed installation and improved holding power
- Ultra sharp point quickly penetrates wood reducing drive time
- Yellow zinc finish

INSTALLATION GUIDELINES

- Use a screwdriver with a torque controlled or precise depth-sensitive clutch and speeds of up to 2500 RPM
- Overdriving may cause a weak connection or thread strip-out of the material
- The drive is finished when the screw is below the work surface

08F200YBTHSS

Interior Trim Head with Nibs Screw

Engineered sheathing to wood



ORDERING INFORMATION

Item Code	Gauge	Length	Thread	Finish	Quantity	Drive Type	Point	Head
08F200YBTHSS	#8	2"	High-Low	Yellow Zinc	4000 Box	#2 Square	Sharp	Trim w/Nibs

TECHNICAL INFORMATION

Ultimate Tensile (lbs)*	Torsional Strength (lbs-in)*
2200	68

*Figures represent ultimate average test results. An appropriate safety factor must be applied for design purposes

Finish	Testing Standard	Corrosion Resistance
Yellow Zinc	ASTM B117 Salt Spray Test	Over 48 Hours without red rust

Reference Dimensions

Length (L):	2.00 in
Head Diameter (A):	0.29 in
Head Height (H):	0.18 in
Major Diameter (D):	0.18 in
Minor Diameter (B):	0.11 in
Threads Per Inch (TPI):	17 threads/in

